

In re Application of: Kowalchik et al.
Attorney Docket No.: EMR-00401

AMENDMENTS TO THE CLAIMS

- Sub
B1
1. (Currently amended) A cache, comprising:
a front-end interface that receives data access requests that specify respective data storage addresses;
a back-end interface that can retrieve data identified by the data storage addresses;
cache storage formed by at least two disks; and
a cache manager that services at least some one of the requests received at the front-end interface using data stored in the cache storage on said at least two disks.
2. (Original) The cache of claim 1, wherein the front-end interface comprises an interface conforming to a protocol.
3. (Currently amended) The cache of claim 2, wherein the protocol comprises at least one of the following: SCSI (Small Computer System Interface), Fibre Channel, ~~Infiniband~~ INFINIBAND, and IDE (Integrated Device Electronics).
- A7
4. (Original) The cache of claim 1, wherein the disks comprise disks having platters less than 3.5 inches in diameter.
5. (Original) The cache of claim 4, wherein the disks comprise disks having at least one of the following platter sizes: 2.5 inches, 1.8 inches, and 1 inch in diameter.
6. (Original) The cache of claim 1, wherein the cache implements a RAID (Redundant Array of Independent Disks) scheme using the disks.
7. (Original) The cache of claim 1, wherein the cache performs at least one of the following operations: requesting data from a back-end storage system, retrieving requested data from the disks, sending data to the back-end system for writing, determining the location of back-end system data within the disks, and removing data from the disks.

In re Application of: Kowalchik et al.
Attorney Docket No.: EMR-00401

8. (Original) The cache of claim 1, wherein the addresses specify storage locations of a back-end storage system that includes a collection of one or more disks.

9. (Original) The cache of claim 1, wherein the requests comprise I/O (Input/Output) requests.

10. (Original) The cache of claim 1, wherein the data storage addresses comprise data storage addresses within an address space.

11. (Original) The cache of claim 10, wherein the address space comprises an address space of back-end storage.

A7
12. (Original) The cache of claim 10, wherein the address space comprises an address space of a different cache.

13. (Original) The cache of claim 1, wherein the cache storage comprises cache storage having more than one disk spindle.

14. (Currently amended) A method of servicing data access requests at a cache, the method comprising:

receiving the data access requests at the cache, the cache having cache storage formed by at least two disks, the requests specifying respective data storage addresses; and

servicing at least ~~some~~ one of the requests using data stored ~~in the disks~~ on said at least two disks.

15. (Original) The method of claim 14, wherein the requests comprise requests conforming to a protocol.

16. (Currently amended) The method of claim 15, wherein the protocol comprises at least one of the following: SCSI, Fibre Channel, ~~Infiniband~~ INFINIBAND, and IDE.

In re Application of: Kowalchik et al.
Attorney Docket No.: EMR-00401

17. (Original) The method of claim 14, wherein the requests comprise at least one read request.

18. (Original) The method of claim 14, wherein servicing the requests comprises retrieving data from the back-end storage and storing the data in at least one of the disks.

19. (Original) The method of claim 18, wherein storing the data comprises storing the data in accordance with a RAID scheme.

20. (Original) The method of claim 14, wherein servicing the requests comprises determining whether the collection of disks currently stores the requested data.

A7
21. (Original) The method of claim 14, wherein the data storage addresses comprise data storage addresses within an address space.

22. (Original) The method of claim 21, wherein the address space comprises an address space of a back-end storage system formed by a collection of disks.

23. (Currently amended) A data storage system, comprising:

a back-end storage system having an address space, addresses in the address space identifying blocks of storage; and

a cache for the back-end storage system having a lesser storage capacity than the back-end storage system, the cache including:

a front-end interface that receives I/O (Input/Output) requests that specify respective addresses of back-end storage blocks;

a back-end interface that communicates with the back-end storage system;
cache storage formed by at least two disks having platter diameters less than 3.5 inches; and

a cache manager that services at least some one of the I/O requests received via the front-end interface using blocks temporarily stored in the cache storage on said at least two disks.

In re Application of: Kowalczyk et al.
Attorney Docket No.: EMR-00401

24. (New) The cache of claim 1, wherein said cache manager simultaneously accesses and retrieves the data stored on said at least two disks for the at least one of the requests received at the front-end interface.

25. (New) The cache of claim 1, wherein said cache further comprises at least one interface conforming to a protocol to allow at least one additional disk to be connected to said cache storage.

A1
26. (New) The cache of claim 1, wherein said cache manager stores identification data identifying addresses within said cache storage where data is stored and the corresponding addresses at a back-end storage area where the data is stored.

27. (New) The method of claim 14, wherein the data stored for the at least one of the requests is simultaneously accessed and retrieved from said at least two disks.

28. (New) The method of claim 14, wherein servicing further comprises storing identification data identifying addresses of data stored within said cache storage and the corresponding addresses at a back-end storage area where the data is stored.

29. (New) The data storage system of claim 23, wherein the cache manager simultaneously accesses and retrieves from said at least two disks the blocks for the at least one of the I/O requests.

30. (New) The data storage system of claim 23, wherein said cache further comprises at least one interface conforming to a protocol to allow at least one additional disk to be connected to said cache storage.

In re Application of: Kowalchik et al.
Attorney Docket No.: EMR-00401

31. (New) The data storage system of claim 23, wherein said cache manager further stores identification data identifying addresses of data stored within said cache storage and the corresponding addresses at said back-end storage area where the data is stored.

32. (New) A data storage system, comprising:

a back-end storage system having an address space, addresses in the address space identifying blocks of storage; and

a plurality of caches for the back-end storage system, each of said plurality of caches having a lesser storage capacity than the back-end storage system, each of said plurality of caches including:

A7 a front-end interface that receives I/O (Input/Output) requests that specify respective addresses of back-end storage blocks;

a back-end interface capable of communicating with one of back-end storage system and another of one of said plurality of caches;

cache storage formed by at least two disks; and

a cache manager that services at least one of the I/O requests received via the front-end interface using blocks temporarily stored on said at least two disks.

33. (New) The data storage system of claim 32, wherein the cache manager simultaneously accesses and retrieves the blocks for the at least one of the I/O requests from said at least two disks.

34. (New) The data storage system of claim 32, wherein:

said plurality of caches are connected in series such that the front-end interface of one of said of plurality of caches is coupled to the back-end interface of another of said plurality of caches;

the front end interface of one of said plurality of caches is coupled to a device making said I/O requests; and,

the back-end interface of one of said plurality of caches is coupled to said back-end storage system.

In re Application of: Kowalchik et al.
Attorney Docket No.: EMR-00401

35. (New) The data storage system of claim 34, wherein upon receiving one of I/O requests at said front-end interface of one of said plurality of caches, the cache manager of said one of plurality of caches sends data corresponding to said one of I/O requests to said device making said one of I/O requests if said data is stored on the cache storage of said one of plurality of caches.

A7 36. (New) The data storage system of claim 34, wherein upon receiving one of I/O requests at said front-end interface of one of said plurality of caches, the cache manager of said one of plurality of caches sends said one of I/O requests to one of back-end storage and another of said plurality of caches coupled to the back-end-interface of said one of plurality of caches if said data is not stored on the cache storage of said one of plurality of caches.

37. (New) The data storage system of claim 32, wherein each of said plurality of caches further comprises at least one interface conforming to a protocol to allow at least one additional disk to be connected to said cache storage.

38. (New) The data storage system of claim 32, wherein said cache manager of each of said plurality of caches further stores identification data identifying addresses of data stored within the corresponding cache storage of each of said plurality of caches and the corresponding addresses at said back-end storage area where the data is stored.